



Advanced Power Strapping Tools

BATTERY HAND TOOL APS-1016 FOR PLASTIC STRAPPING



TECHNICAL DATA

Weight	4.0 kg (9.9 lbs.) (incl. battery)
Dimensions:	Length 258 mm (10.1 "); Width 142 mm (5 .6"); Height 166 mm (6 .5").
Strap tension	400-2500 N (88-550 lbs.).
Tension speed	250 mm/s (9.8"/s)
Sealing	Friction welded
Joint efficiency	Up to 90% of strapping breaking strength.
BATTERY BOSCH 18 V Li-Ion.	
Strappings with one battery charge:	120-250 (PP); 80-150 (PET), Depending on strap, strap tension and package.
Service life	Up to approx. 2000 charging.
BATTERY CHARGER BOSCH BC 630	
Voltage	100-240 V; 50-60Hz.
Charging time	Approx. 25-30 minutes.
PLASTIC STRAP	
Strap quality	Polypropylene (PP). Polyester (PET)
Strap width adjustable to	10 mm (0 .394") (PET), 13 mm (1/2") (PET, PP) 16 mm (5/8") (PET, PP)
Strap thickness	Polypropylene 0.7-1 .0 mm (.028"- .039"). Polyester 0.7-1.3 mm (.028"- .051